




|   |       |       |                                      |                |
|---|-------|-------|--------------------------------------|----------------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) | Depth | 1 000 | range 250 nm to 800 nm, at full-load |                |
| Claim of equivalent power <sup>(a)</sup>  |       | -     | If yes, equivalent power (W)         | -              |
|   |       |       | Chromaticity coordinates (x and y)   | 0,311<br>0,331 |
| <b>Parameters for LED and OLED light sources:</b>   |       |       |                                      |                |
| R9 colour rendering index value   |       | 81    | Survival factor                      | 1,00           |
| the lumen maintenance factor  |       | 0,96  |                                      |                |

(a) '-': not applicable;

(b) '-': not applicable;



Model placed on the Union market from 05/07/2025



**EPREL registration number:** 2407753

<https://eprel.ec.europa.eu/qr/2407753>

**Supplier:** V-TAC Europe Ltd (Manufacturer)

**Website:** [www.v-tac.eu](http://www.v-tac.eu)

**Customer care service:**

**Name:** V-TAC Europe

**Website:** [www.v-tac.eu](http://www.v-tac.eu)

**Email:** [office@v-tac.eu](mailto:office@v-tac.eu)

**Phone:** +359290566

**Address:**

bul. Rozhen 41

Sofia

Bulgaria