

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 4912

Type of light source:

| | | | |
|---|--|---------------------------------|------|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | L/N connect line (accessory also have fast connector) | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |

Product parameters

| Parameter | Value | Parameter | Value |
|--|----------------------|--|-------|
| General product parameters: | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 12 | Energy efficiency class | G |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 900 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 000 |
| On-mode power (P_{on}), expressed in W | 12,0 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |

| | | | | |
|--|--------|---------------------------------------|---|------------------------|
| Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) | Height | 24 | Spectral power distribution in the range 250 nm to 800 nm, at full-load | See image in last page |
| | Width | 140 | | |
| | Depth | 140 | | |
| Claim of equivalent power ^(a) | | - | If yes, equivalent power (W) | - |
| | | | Chromaticity coordinates (x and y) | 0,329 0,352 |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value | -5 | Survival factor | 1,00 | |
| the lumen maintenance factor | 0,96 | | | |
| Parameters for LED and OLED mains light sources: | | | | |
| displacement factor (cos ϕ_1) | 0,43 | Colour consistency in McAdam ellipses | 6 | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W) | - | |
| Flicker metric (Pst LM) | 0,1 | Stroboscopic effect metric (SVM) | 0,0 | |

(a) '-': not applicable;

(b) '-': not applicable;

